



SAFETY DATA SHEET

Floor Paint

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Floor Paint
Product description : Paint
Product type : Liquid.
UFI : V91W-T09N-V00S-DKTF
Product code : FLS0003

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer Industrial Professional	
Uses advised against	Reason
None identified.	-

1.3 Details of the supplier of the safety data sheet

Floorsaver Ltd,
Eastgate Court
195-205 High Street
Guildford
Surrey
GU1 3EH
United Kingdom
Telephone no: 0345 4509888
Email: info@floorsaver.co.uk

Floorsaver
Kränkelsweg 14
41748 Viersen
Deutschland
Telephone no.: 02162-5746666
info@floorsaver.de

e-mail address of person responsible for this SDS : rpmeurohas@rustoleum.eu

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number Ireland : 809 2166
Available 8am to 10pm 7 days per week

Supplier

Telephone number Ireland : +353 19014670
Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Sens. 1, H317

STOT SE 3, H336


The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.

Precautionary statements

General : P103 - Read carefully and follow all instructions.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention : P280 - Wear protective gloves.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 - Use only outdoors or in a well-ventilated area.

Response : P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage : P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : ☒ hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics
(Z)-.alpha.-(3-Carboxy-1-oxo-2-propenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl) alkyl(C9-11) ethers
neodecanoic acid, cobalt salt
maleic anhydride

Supplemental label elements : ☒ UH066 - Repeated exposure may cause skin dryness or cracking.

Supplemental label elements : Not applicable.

Supplemental label elements : Detergents - Regulation (EC) No 907/2006

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Floor Paint

SECTION 2: Hazards identification

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. : Not applicable

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture
Ireland

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	-	[1] [2]
reaction mass of ethylbenzene and xylene	EC: 905-588-0	≤5	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1]
hydrocarbons, C10-C13, n-/iso-/ cyclo-alkanes, < 2% aromatics	REACH #: 01-2119457273-39 CAS: 64742-48-9 List #: 918-481-9	≤1	Asp. Tox. 1, H304 EUH066	-	[1]
(Z)-.alpha.-(3-Carboxy-1-oxo-2-propenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl)alkyl(C9-11) ethers	CAS: 709014-50-6	≤1	Skin Sens. 1, H317	-	[1]
naphtha (petroleum), heavy alkylate C9-C11	REACH #: 01-2119471991-29 EC: 923-037-2 CAS: 64741-65-7	≤0,3	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1] [2]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0,3	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 3,	ATE [Oral] = 1098 mg/kg	[1] [2]

Floor Paint

SECTION 3: Composition/information on ingredients

neodecanoic acid, zirconium salt	REACH #: 01-2120770770-52 EC: 254-259-1 CAS: 39049-04-2	≤0,3	H412 Acute Tox. 4, H302	ATE [Oral] = 500 mg/kg	[1] [2]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0,1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (inhalation) EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0,001%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

Type

- [1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit

List numbers have no legal significance.
Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

SECTION 4: First aid measures

as a collar, tie, belt or waistband.

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
sulfur oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

SECTION 5: Firefighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not

SECTION 7: Handling and storage

reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria		
Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits / Biological exposure indices

Ireland

Product/ingredient name	Exposure limit values
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	NAOSH (Ireland, 8/2007) OELV-8hr 8 hours: 575 mg/m³ (as Stoddard solvent, low boiling naphtha (100 ppm)). Recommended by manufacturer (Ireland, 2009) [hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics] TWA 8 hours: 1200 mg/m³ (as hydrocarbon mixture (A) (197 ppm)). Form: Vapour.
naphtha (petroleum), heavy alkylate C9-C11	OEL Reference is obsolete or not recognized. Consider revising. (Europe) Notes: Recommended by manufacturer TWA 8 hours: 1300 mg/m³ ((200 ppm)). Form: Vapour.
neodecanoic acid, cobalt salt	NAOSH (Ireland, 4/2024) [cobalt & cobalt compounds] Carc 1B, Repr 1B. Sensitiser. Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 0,02 mg/m³ (as Co).
neodecanoic acid, zirconium salt	NAOSH (Ireland, 4/2024) [zirconium compounds] Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 5 mg/m³ (as Zr). OELV 15 minutes: 10 mg/m³ (as Zr).
maleic anhydride	NAOSH (Ireland, 4/2024) Sensitiser. Notes: Advisory

Floor Paint	
SECTION 8: Exposure controls/personal protection	
	Occupational Exposure Limit Values (OELVs) OELV 8 hours: 0,01 ppm. Form: The Inhalable Fraction and Vapour note is used when a material exerts sufficient vapour pressure such that it may be present in both particle and vapour phases..

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Product/ingredient name	Result	Value	Effects
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics reaction mass of ethylbenzene and xylene	DNEL - Workers - Long term - Dermal	280 mg/kg	<u>Effects:</u> Systemic
	DNEL - Workers - Short term - Inhalation	871 mg/m³	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Oral	125 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Inhalation	185 mg/m³	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Dermal	125 mg/kg	<u>Effects:</u> Systemic
	DNEL - Workers - Short term - Inhalation	442 mg/m³	<u>Effects:</u> Local
	DNEL - Workers - Short term - Inhalation	442 mg/m³	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Inhalation	221 mg/m³	<u>Effects:</u> Local
	DNEL - Workers - Long term - Inhalation	221 mg/m³	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal	212 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Short term - Inhalation	260 mg/m³	<u>Effects:</u> Local
	DNEL - General population - Short term - Inhalation	260 mg/m³	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation	65,3 mg/m³	<u>Effects:</u> Local

SECTION 8: Exposure controls/personal protection

hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	DNEL - General population - Long term - Inhalation	65,3 mg/m ³	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Dermal	125 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Oral	12,5 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal	208 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Dermal	125 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation	185 mg/m ³	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Oral	125 mg/m ³	<u>Effects:</u> Systemic
neodecanoic acid, cobalt salt	DNEL - Workers - Long term - Inhalation	871 mg/m ³	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Inhalation	273 µg/m ³	<u>Effects:</u> Local
	DNEL - General population - Long term - Inhalation	43 µg/m ³	<u>Effects:</u> Local
maleic anhydride	DNEL - General population - Long term - Oral	0,032 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - Workers - Short term - Inhalation	0,8 mg/m ³	<u>Effects:</u> Systemic
	DNEL - Workers - Short term - Dermal	0,04 mg/kg	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Inhalation	0,4 mg/m ³	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation	0,05 mg/m ³	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Oral	0,06 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation	0,08 mg/m ³	<u>Effects:</u> Local
	DNEL - Workers - Long term - Inhalation	0,081 mg/m ³	<u>Effects:</u> Local
	DNEL - General population - Short term - Oral	0,1 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Short term - Dermal	0,1 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Long term - Dermal	0,1 mg/kg bw/day	<u>Effects:</u> Systemic

SECTION 8: Exposure controls/personal protection

	DNEL - Workers - Long term - Dermal	0,2 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Short term - Inhalation	0,2 mg/m³	Effects: Local

PNECs

Product/ingredient name	Result	Value	Remarks
Reaction mass of ethylbenzene and xylene	Fresh water	0,327 mg/l	-
	Marine water	0,327 mg/l	-
	Fresh water sediment	12,46 mg/kg	-
	Marine water sediment	12,46 mg/kg	-
	Soil	2,31 mg/kg	-
	Sewage Treatment Plant	6,58 mg/l	-
neodecanoic acid, cobalt salt	Fresh water	1,06 µg/l	-
	Marine water	2,36 µg/l	-
	Sewage Treatment Plant	0,37 mg/l	-
	Fresh water sediment	53,8 mg/kg dwt	-
	Marine water sediment	69,8 mg/kg dwt	-
	Soil	10,9 mg/kg dwt	-
maleic anhydride	Fresh water	0,04281 mg/l	-
	Marine water	0,004281 mg/l	-
	Soil	0,0415 mg/l	-
	Fresh water sediment	0,334 mg/kg	-
	Marine water sediment	0,0334 mg/kg	-
	Sewage Treatment Plant	44,6 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres. (EN 1149-1)

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140)

- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Floor Paint

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

- Physical state : Liquid.
- Colour : Various
- Odour : Not available.
- Odour threshold : Not available.
- Melting point/freezing point : Not available.
- Initial boiling point and boiling range : Not available.

Ingredient name	°C	°F	Method
Reaction mass of ethylbenzene and xylene	136 to 145	276,8 to 293	Literature

- Flammability (solid, gas) : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
- Lower and upper explosion limit : Not available.
- Flash point : Closed cup: 40°C (104°F)
- Auto-ignition temperature : Not relevant due to nature of the product.
- Decomposition temperature : Not available.
- pH : Not applicable. [Literature]
- pH : Justification : Product is non-soluble (in water).
- Viscosity : Dynamic (room temperature): 500 to 625 mPa·s [ASTM D562 [KU]]
Kinematic (room temperature): 464 to 580 mm²/s [calculated.]
Kinematic (40°C): 350 mm²/s

Solubility(ies) :

Media	Result
cold water	Not soluble
hot water	Not soluble

- Solubility in water : Not available.
- Miscible with water : No.
- Partition coefficient: n-octanol/ water : Not applicable.
- Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	0,75006 to 2,25018	0,1 to 0,3	calculated.			

- Evaporation rate : Not available.
- Relative density : 0,9 to 1
- Density : 1,017 to 1,077 g/cm³ [20°C (68°F)] [DIN 53217]
- Vapour density : Not available.
- Explosive properties : Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
- Oxidising properties : Not available.
- Particle characteristics
- Median particle size : Not applicable.

Floor Paint

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials:
oxidising materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Value
Reaction mass of ethylbenzene and xylene	Rabbit - Dermal - LD50	12126 mg/kg
neodecanoic acid, cobalt salt	Rat - Female - Oral - LD50	1098 mg/kg
maleic anhydride	Rat - Oral - LD50	400 mg/kg
	Rabbit - Dermal - LD50	2620 mg/kg

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Floor Paint	N/A	22079,5	N/A	220,8	N/A
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	10000	N/A	N/A	N/A	N/A
reaction mass of ethylbenzene and xylene	N/A	1100	N/A	11	N/A
neodecanoic acid, cobalt salt	1098	N/A	N/A	N/A	N/A
maleic anhydride	400	2620	N/A	N/A	N/A

Skin corrosion/irritation

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name **Conclusion/Summary**

SECTION 11: Toxicological information

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	May cause mild skin irritation
reaction mass of ethylbenzene and xylene	Harmful in contact with skin
naphtha (petroleum), heavy alkylate C9-C11	Non-irritating to the skin.
neodecanoic acid, cobalt salt	Non-irritating to the skin.

Serious eye damage/eye irritation

Product/ingredient name	Result	Exposure	Observation
maleic anhydride	Rabbit - Eyes - Severe irritant	Amount/concentration applied: 1 %	-

Conclusion/Summary [Product]	: Based on available data, the classification criteria are not met.
Ingredient name	Conclusion/Summary
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Non-irritating to the eyes.
naphtha (petroleum), heavy alkylate C9-C11	Non-irritating to the eyes.
neodecanoic acid, cobalt salt	Non-irritating to the eyes.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product]	: May cause drowsiness or dizziness.
Ingredient name	Conclusion/Summary
reaction mass of ethylbenzene and xylene	Harmful by inhalation.

Respiratory or skin sensitization

Product/ingredient name	Species - Route of exposure	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Rabbit - skin	Result: Not sensitizing

Skin	
Conclusion/Summary [Product]	: May cause an allergic skin reaction.
Ingredient name	Conclusion/Summary
naphtha (petroleum), heavy alkylate C9-C11	Non-sensitiser to skin.
neodecanoic acid, cobalt salt	May cause sensitisation by skin contact.

Respiratory	
Conclusion/Summary [Product]	: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product]	: Based on available data, the classification criteria are not met.
Ingredient name	Conclusion/Summary
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Not mutagenic in a standard battery of genetic toxicological tests.

Carcinogenicity

Floor Paint

SECTION 11: Toxicological information

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name	Conclusion/Summary
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	No carcinogenic effect.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	STOT SE 3, H336 (Narcotic effects)
reaction mass of ethylbenzene and xylene	STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
reaction mass of ethylbenzene and xylene	STOT RE 2, H373
neodecanoic acid, cobalt salt	STOT RE 1, H372
maleic anhydride	STOT RE 1, H372 (inhalation)

Aspiration hazard

Product/ingredient name	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	ASPIRATION HAZARD - Category 1
reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	ASPIRATION HAZARD - Category 1
naphtha (petroleum), heavy alkylate C9-C11	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness

SECTION 11: Toxicological information

Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.
<u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u>	
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Potential chronic health effects</u>	
Not available.	
Conclusion/Summary [Product]	: Based on available data, the classification criteria are not met.
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.	
Conclusion/Summary [Product]	: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.	
----------------	--

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species
Hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics reaction mass of ethylbenzene and xylene	Acute - NOEC 100 mg/l [72 hours]	Algae
	Chronic - NOEC 0,23 mg/l	Daphnia spec.
	Chronic - NOEC 0,131 mg/l	Fish
	NOEC 0,44 mg/l [72 hours]	Algae
	Chronic - NOEC 0,96 mg/l [7 days]	Daphnia spec.
	Chronic - NOEC 1,3 mg/l [56 days]	Fish - Rainbow trout (oncorhynchus mykiss)

Floor Paint

SECTION 12: Ecological information

naphtha (petroleum), heavy alkylate C9-C11	Chronic - NOEC 1,17 mg/l [7 days]	Daphnia spec. - Zebra barbel
maleic anhydride	Acute - EC50 >1000 mg/l [24 hours]	Daphnia spec.
	Acute - LC50 - Fresh water 230 ppm [96 hours]	Fish - Western mosquitofish - Adult

Conclusion/Summary [Product]

: Based on available data, the classification criteria are not met.

Ingredient name

neodecanoic acid, cobalt salt

Conclusion/Summary

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	-	>80% [28 days] - Readily
	-	>80% [28 days] - Readily

Conclusion/Summary [Product]

: This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Ingredient name

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics

Conclusion/Summary

Rapidly lost by degradation and volatilisation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	-	100%; <28 day(s)	Readily
naphtha (petroleum), heavy alkylate C9-C11	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	5 to 6.7	10 to 2500	High
reaction mass of ethylbenzene and xylene	3,6	-	Low
naphtha (petroleum), heavy alkylate C9-C11	>3	-	Low
neodecanoic acid, cobalt salt	-	15600	High
maleic anhydride	-2,78	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
maleic anhydride	1,1	11,4841

Results of PMT and vPvM assessment

Date of issue/Date of revision

: 26/02/2026

Date of previous issue

: 3/10/2024

Version

: 2.01

17/24

Floor Paint

SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	No	No	No	No	No	No
reaction mass of ethylbenzene and xylene	No	No	No	No	No	No	No
hydrocarbons, C10-C13, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	No	No	No	No	No	No
(Z)-.alpha.-(3-Carboxy-1-oxo-2-propenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl)alkyl(C9-11) ethers	No	No	No	No	No	No	No
naphtha (petroleum), heavy alkylate C9-C11	No	No	No	No	No	No	No
neodecanoic acid, cobalt salt	No	No	No	No	No	No	No
maleic anhydride	No	No	No	No	No	No	No

Mobility : Volatile.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	N/A	No	No	No	N/A	No
reaction mass of ethylbenzene and xylene	N/A	N/A	N/A	Yes	N/A	N/A	N/A
hydrocarbons, C10-C13, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	N/A	N/A	No	N/A	N/A	N/A
(Z)-.alpha.-(3-Carboxy-1-oxo-2-propenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl)alkyl(C9-11) ethers	No	N/A	N/A	No	N/A	N/A	N/A
naphtha (petroleum), heavy alkylate C9-C11	No	N/A	N/A	No	N/A	N/A	N/A
neodecanoic acid, cobalt salt	N/A	N/A	Yes	Yes	N/A	N/A	Yes
maleic anhydride	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	No	No	No	No	No	No
reaction mass of ethylbenzene and xylene	No	No	No	No	No	No	No
hydrocarbons, C10-C13, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	No	No	No	No	No	No
(Z)-.alpha.-(3-Carboxy-1-oxo-2-propenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl)alkyl(C9-11) ethers	No	No	No	No	No	No	No

Floor Paint

SECTION 12: Ecological information

naphtha (petroleum), heavy alkylate C9-C11	No	No	No	No	No	No	No
neodecanoic acid, cobalt salt	No	No	No	No	No	No	No
maleic anhydride	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT

Floor Paint				
SECTION 14: Transport information				
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

Additional information ADR

Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Limited quantity	: 5L
Transport Category	: 3
Hazard identification number	: 30
Classification code	: F1
ADR Label Model Number	: 3
Excepted Quantity	: E1
Tunnel code	: (D/E)
Packing instructions	: P001, IBC03, LP01, R001
Mixed Packing Provisions	: MP19
Special Packing Provisions	: PP1
Special provisions	: 163, 367, 650
Remarks	: Exempted according to 2.2.3.1.5 (Viscous substance exemption)

This class 3 material is not subject to regulation in packagings up to 450 L.

Additional information ADN

Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Limited quantity	: 5L
Classification code	: F1
Special provisions	: 163, 367, 650
Remarks	: ≤ 5L: Limited Quantity

Additional information IMDG

Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

Limited quantity	: 5L
Emergency schedules	: F-E, S-E
Special provisions	: 163, 223, 367, 955
Remarks	: ≤ 5L: Limited Quantity - IMDG 3.4

Additional information IATA

Passenger and Cargo Aircraft	: Quantity limitation 60L Packaging instruction 355
Cargo aircraft	: Quantity limitation 220L Packaging instruction 366

Floor Paint

SECTION 14: Transport information

- Limited Quantities - Passenger Aircraft Special provisions : ☒ Quantity limitation 10L Packaging instruction Y344
: ☒ A3, A72, A192
- 14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles
- | Product/ingredient name | % | Designation [Usage] |
|-------------------------|-----|---------------------|
| Floor Paint | ≥90 | 3 |
- Labelling : Not applicable.
Synthetic polymer microparticles - Designation 78
Generic identity of polymer(s) : ☒ Not applicable.
Total percentage of synthetic polymer microparticles : ☒ Not applicable.
- Other EU regulations
VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture : IIA/i. One-pack performance coatings. EU limit value for this product : 500g/l (2010.) This product contains a maximum of 450 g/l VOC.
Industrial emissions (integrated pollution prevention and control) - Air : Not listed
Industrial emissions (integrated pollution prevention and control) - Water : Not listed
Explosive precursors : Not applicable.
Ozone depleting substances (EU 2024/590)
Not listed.
Prior Informed Consent (PIC) (649/2012/EC)

Floor Paint

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

Ireland

Biocidal products regulation : Not applicable.

Product/ingredient name	List name	Name on list	Classification	Notes

References : Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001 (S.I. No. 619 of 2001)
Safety, Health and Welfare at Work (Carcinogens) Regulations 2001 (S.I. No. 78 of 2001)
Safety, Health and Welfare at Work (General Application) Regulations 2007
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878
REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name	Ingredient name	Status
Not listed.		

CN code : 3208 90 91 00

Inventory list

- Australia : At least one component is not listed.
- Canada : At least one component is not listed.
- China : At least one component is not listed.
- Eurasian Economic Union : Russian Federation inventory: Not determined.
- Japan : Japan inventory (CSCL): At least one component is not listed.
Japan inventory (ISHL): At least one component is not listed.
- New Zealand : At least one component is not listed.
- Philippines : At least one component is not listed.
- Republic of Korea : At least one component is not listed.
- Taiwan : At least one component is not listed.
- Thailand : Not determined.
- Turkey : Not determined.

Floor Paint

SECTION 15: Regulatory information

United States : Not determined.
Viet Nam : Not determined.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Skin Sens. 1, H317 STOT SE 3, H336	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

Ireland	
Full text of abbreviated H statements	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. EUH071 Corrosive to the respiratory tract.

Floor Paint

SECTION 16: Other information

Full text of classifications [CLP/GHS]	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
	Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
	Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
	Skin Sens. 1	SKIN SENSITISATION - Category 1
	Skin Sens. 1A	SKIN SENSITISATION - Category 1A
	STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
	STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
	STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 27/02/2026

Date of issue/ Date of revision : 26/02/2026

Date of previous issue : 3/10/2024

Version : 2.01

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.