



Product Information Sheet:

Mouldable Concrete Filler

10kg



Floorsaver Mouldable Concrete Filler is a high-strength, polymer-cement repair material for step nosings, kerbs and damaged stonework. Its unique pliable mix lets you use only what you need with no waste, easily moulded by hand or tool. Non-dusting, paintable, hard in 1 hour and fully solid in 2 hours.

- Easy to mix by just adding water and dries rapidly
- No priming, just push it in and smooth it off
- High strength
- No wastage
- Can be used both inside and outside even in cold conditions
- Repairs 5mm – 100mm deep in one go

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- Use at temperatures above 5°C.
- Use a stiff brush to remove any loose dirt, dust or other contamination. Scrape off as much existing paint as possible.
- Dampen dry surfaces with cold water.

Step 2 - Mixing:

- Only mix as much as you can use in 5-10 minutes.
- The mix ratio is 7 parts powder to 1 part water by volume, or 10 parts powder to 1 part water by weight. A 10kg unit will produce approximately 5L of repair material and cover approximately 1m² at a depth of 5mm.
- It's important to add the powder to the water, not the other way round!
- You can use some powder from the pack and mix with a little water to get the feel of it. It's probably easiest to wear disposable gloves to mix and knead it by hand. Or use a paper cup to help get your 7 to 1 ratio by volume.
- If your initial mix is too dry and crumbly add some water immediately. If the mix is too runny, add some more powder.
- The secret is not to mix any further after 2-3 minutes, since the mixture will have started curing and the structure of the mix will be damaged and crumble.

Step 3 - Application:

- Dampen the area to be repaired with water.
- Push the mixture into place using a wet gloved hand or trowel, then shape as required.
- Each mix is usable for 5-10 minutes at 15°C - 20°C.
- Wash tools in water.

DRYING TIMES:

INITIAL SET	10 minutes at 15°C - 20°C
HARD DRY	1 hour at 15°C - 20°C
FULL STRENGTH	2 hours at 15°C - 20°C

At 10°C and below, drying times will be longer.
As a guide allow 24 hours at 5°C.
Floorsaver Mouldable Concrete Filler can be painted after 2 hours.

SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments or need advice, please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888
IE: 0818 543 250

info@floorsaver.co.uk
info@floorsaver.ie

floorsaver.co.uk
floorsaver.ie