



Product Information Sheet:

Epoxy Floor Paint & Epoxy Floor Paint Anti Slip 2.5L & 5L



Available in 190 RAL shades



Floorsaver Epoxy Floor Paint is a heavy-duty, water-based two-pack epoxy for high-traffic internal concrete floors. It provides a tough, mid-gloss finish that dustproofs, protects, and makes cleaning easier. Suitable for bare concrete or sound existing coatings, it's ideal for demanding areas such as forklift zones and vehicle parking.

- 2 pack water based epoxy for heavy wear areas, such as warehouses, workshops, showrooms, etc.
- Good general chemical resistance
- Easy roller application
- Glossy finish
- Choose Epoxy Floor Paint Anti Slip for wet or slippery areas
- 2.5L covers up to 15m² per coat
- 5L covers up to 30m² per coat

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- On bare, reasonably clean concrete wash with Floorsaver Floor Etcher. This cleans and keys the surface.
- For greasy or previously painted floors, clean with Floorsaver Cleaner & Degreaser, scraping off any loose paint, dust or dirt. Lightly sand glossy paint to dull down the shine and roughen it up.
- New concrete should be at least 2 months old and always washed with Floorsaver Floor Etcher to reduce alkalinity and to remove any weak, loose cement deposits.

Step 2 – Repairs

- Fill holes using Floorsaver Pourable Concrete Filler.

Step 3 - Application:

- Apply at a minimum temperature of 15°C, in a well ventilated area.
- If the floor is still damp from cleaning, that's fine as this is a water-based epoxy, but do not apply it to floors with rising damp.
- For both the 2.5L and 5L pack sizes there is a large tin of coloured curing agent and a smaller tin of resin. Stir the contents of the large tin, then add the contents of the small resin tin.
- Give a good stir with something wide, like a wooden batten or a paint stirrer. If you use an electric paint mixer, also scrape around the sides and bottom of the tin to make sure it's all mixed in.
- Now it's mixed you've got 2 hours to use it before it becomes unusable. Tip it into a roller tray or scuttle.
- Use a brush around the edges and a medium pile roller for the floor.

For Epoxy Floor Paint Anti Slip:

- Mix the resin and curing agent together, then add all the anti-slip aggregate for 5L units or half for 2.5L, stirring thoroughly. Use immediately. The aggregate becomes more visible as the paint dries, and two coats are recommended for a consistent anti-slip finish.

CURING TIMES:

RECOAT 12 hours at 15°C - 20°C
The second coat should be applied within 5 days of the first coat.

WALK ON 16 - 24 hours at 15°C - 20°C

CARS 2 - 3 days at 15°C - 20°C

FULL HARDNESS,
SCRATCH & CHEMICAL RESISTANCE 7 days at 15°C - 20°C

WE DON'T RECOMMEND:

- Using outside – it can fade under UV rays.
- Applying to self-levelling floor screeds.
- Applying to hard, very smooth power floated concrete where paint can't sink into the surface. If in doubt, tip a cup of water onto the floor to see if it soaks in or not.
- Applying to very weak, crumbly or contaminated concrete since it may not be possible to prepare it well enough for the Epoxy Floor Paint to perform.
- Applying to metal since it can cause rusting.
- Using in enclosed spaces with little or no ventilation.

SHELF LIFE:

36 months, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888

IE: 0818 543 250

info@floorsaver.co.uk

info@floorsaver.ie

floorsaver.co.uk

floorsaver.ie