



Product Information Sheet:

Hazard Paint & Hazard Paint Anti Slip 2.5L & 5L

**Safety
Yellow**

While great care is taken with the colour sample shown, no guarantee can be given that it represents exactly the colour offered.



TOUGH, GLOSSY, POLYURETHANE FORMULA FOR CONCRETE AND SIMILAR SURFACES.

Floorsaver Hazard Paint comes in bright yellow which is ideal for line marking, hatching, highlighting kerbs, step edges, pillars and obstructions throughout the workplace.

- Improve safety indoors and out
- Tough single pack polyurethane
- Easy brush or roller application
- Only one coat is normally needed
- 2.5L covers up to 20m² per coat
- 5L covers up to 40m² per coat
- Suitable for bare concrete, existing well bonded paint, masonry and most metal surfaces

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- Surfaces should be clean, dry and dust free.
- If using as a line marker or to paint a kerb or minor obstruction, the best way of cleaning is by using a stiff or wire brush and sweeping away any dust. Grease or oil can be removed by using Floorsaver Cleaner & Degreaser.
- For larger areas:
On bare, reasonably clean concrete wash with Floorsaver Floor Etcher - this cleans and keys the surface.
On greasy or previously painted floors clean with Floorsaver Cleaner & Degreaser, scraping off any loose paint, dust or dirt.
New concrete should be at least 2 months old and always washed with Floorsaver Floor Etcher to reduce alkalinity.

Step 2 - Repairs

- Fill holes using Floorsaver Pourable Concrete Filler.

Step 3 - Application:

- Check the surface is dry before painting and that the temperature is a minimum of 15°C.
- Concrete or similar surfaces should be sufficiently porous for the product to 'soak in' to get a key.
- If using a paint brush one coat should be sufficient, but if you are using this over a darker previously painted floor, or applying it by roller, allow for two coats to get a solid colour. Leave for 16 hours (at 15°C - 20°C) before applying the second coat. The second coat must be applied within 5 days of the first coat.
- Clean equipment with White Spirit.

For Hazard Paint Anti Slip:

- Add all the anti-slip aggregate for 5L units or half for 2.5L, stirring thoroughly. Use immediately. The aggregate becomes more visible as the paint dries, and two coats are recommended for a consistent anti-slip finish.

DRYING TIMES:

TOUCH DRY 10 hours at 15°C - 20°C.

LIGHT TRAFFIC 24 hours at 15°C - 20°C

FULL USE 36 hours at 15°C - 20°C.

SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888

IE: 0818 543 250

info@floorsaver.co.uk

info@floorsaver.ie

floorsaver.co.uk

floorsaver.ie