



Product Information Sheet: Multi-Purpose Paint 1L



Available in 190 RAL shades



Floorsaver Multi-Purpose Paint is an all-in-one paint designed for versatility and durability. Suitable for most surfaces with minimal preparation needed, this easy to use single pack paint offers lasting protection and an attractive gloss finish.

- For internal or external use
- Ideal for fences, pipework, gates, garden furniture, and outdoor metalwork
- Resistant against rain, sun, and temperature changes
- Single pack – use as needed, then reseal airtight and store at ambient temperature to use again.
- Easy roller or brush application
- Available in 190 RAL colours
- 10m² coverage per 1L per coat

HERE'S HOW TO USE IT:

Step 1 - Preparation:

Multi-Purpose Paint is self-priming. Multiple coats can be used if full coverage is not achieved in one coat.

Painted Surfaces – Using a wire brush or scraper, get rid of any peeling paint or loose rust. Check remaining paint is well bonded. Very smooth, glossy paint must be lightly abraded to provide a key.

Bare Metal - Remove grease and oil with Floorsaver Cleaner & Degreaser or similar, prep smooth metal with a wire-brush to improve adhesion, then rinse away all residues. Ensure the surface is clean, dry and free of loose material before painting.

Copper & Brass - If the surface has a green patina, this should be removed with phosphoric acid prior to painting.

Stainless Steel - Bristle blasting is recommended to provide a surface where the paint will adhere sufficiently.

Wood - Ensure the surface is clean and dry. Porous wood surfaces may require multiple coats to achieve desired finish.

Bare concrete - Wash with Floorsaver Floor Etcher to clean and key the surface. Greasy or previously painted floors should be cleaned with Cleaner & Degreaser and any loose paint, dust or dirt removed. New concrete must be at least 2 months old and etched to reduce alkalinity. Multiple coats may be needed for the desired finish.

Step 2 - Application:

- Check the surface is clean and dry before painting and that the temperature is a minimum of 15°C.
- Stir the paint thoroughly.
- Do not thin.
- Tip into a roller tray.
- Cut in around the edges with a brush.
- Apply to the area using a paint roller, working well into the surface.
- Clean equipment with White Spirit.

DRYING TIMES:

RECOAT	24 hours at 15°C - 20°C.
TOUCH DRY	8 hours at 15°C - 20°C
HARD DRY	24 hours at 15°C - 20°C

Please allow full hardness to develop before use. Even after drying, it takes a few days to achieve optimal hardness and resistance. Avoid scratching, heavy loads, impacts, or cleaning chemicals during this time.

SHELF LIFE:

3 years, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve great results.

If you have any comments or need advice, please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888
IE: 0818 543 250

info@floorsaver.co.uk
info@floorsaver.ie

floorsaver.co.uk
floorsaver.ie