



Product Information Sheet:

Pourable Concrete Filler

10kg & 25kg



Floorsaver Pourable Concrete Filler gives rapid, reliable repairs for damaged concrete. Designed for holes deeper than 5mm, this cement-based formula is reinforced with polymers and accelerators for exceptional strength. Simply mix with water and pour into place. Walkable in just 1 hour and ready for heavy use after 4 hours, it's ideal for high-traffic areas such as warehouses, factories, car parks and driveways.

- Mix and pour – no primer required
- Help it into place with a trowel and it will 'self-level'
- Just add water and mix in the bucket provided
- For internal or external use
- Fill holes 5mm to 100mm in one go
- Non-dusting

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- Minimal preparation is required. Floorsaver Pourable Concrete Filler is easy to use and very forgiving. Sweep out any loose stuff from the hole and that's about it.
- For heavy-traffic repairs such as forklift areas, chip the edges so the filler is at least 3–5 mm thick. Remove old paint and any concrete contaminated with oil or fats. No priming is required, and the filler can be applied to damp (but not wet) surfaces.

Step 2 - Mixing:

- Take the powder bag out of the bucket. Mix 1 part water to 3 parts powder, adding the water with a jug or an old cup. It's best to start with a small mix until you get the hang of it.
- Use a mixing blade in an electric drill. Add water gradually to the powder (in that order) and mix until it's pourable, like runny porridge. Add a little more water if too stiff or more powder if too runny.
- Only mix up what you can use within 10 minutes. Don't remix it once you have completed your initial mix (since the mixture will have started curing).

Step 3 - Application:

- Pour it into the hole. If you've got the mix right it will 'self-level' although you might have to spread it over large areas with a trowel.
- 10kg covers approx. 0.2m² at 25 mm thick, 25kg covers approx. 0.5m² at 25 mm thick.
- Clean tools in water.

DRYING TIMES (at 10°C):

INITIAL SET	Dries quickly so only mix what you can use within 10 minutes.
FOOT TRAFFIC	1 hour
HEAVY TRAFFIC	Vehicles and forklifts – 4 hours.
PAINTING	Allow 12 hours if you want to paint over the repair. At 5°C allow 24 hours.

SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

WE DON'T RECOMMEND:

- Using at temperatures below 5°C.
- Using on slopes, step nosings, etc. since the product is pourable. For this type of repair use Floorsaver Mouldable Concrete Filler.
- Using at a depth of more than 100mm in one go. For very deep holes, allow a 100mm thick layer to dry for 12 hours, at a minimum temperature of 10°C, before applying the next.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments or need advice, please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888

IE: 0818 543 250

info@floorsaver.co.uk

info@floorsaver.ie

floorsaver.co.uk

floorsaver.ie