



Product Information Sheet:

Universal Concrete Primer

5L

PACK CONTENTS:

- 1 x tin of curing agent
- 1 x tin of resin



Floorsaver Universal Concrete Primer is a clear, water-based, two-part epoxy that penetrates porous concrete to bind and seal it in one step. Ideal for dusty or highly absorbent floors, it reduces porosity and improves paint finish when used as a first coat.

- Helps remove the porosity from highly-absorbent concrete and sand and cement screeds prior to painting
- Ideally suited for use before applying Floorsaver Epoxy Floor Paint onto very porous surfaces
- Water based epoxy resin primer
- For internal use
- Easy roller application
- 5L covers 30m² (coverage can vary depending on the condition of the floor to which it is being applied to)

HERE'S HOW TO USE IT:

Step 1 – Preparation:

- Surfaces should be clean and as dry as possible. Some residual damp is alright, but drying the floor helps the product absorb properly.
- Use Floorsaver Cleaner & Degreaser to remove oil and grease.
- Floorsaver Universal Concrete Primer is designed for very porous bare concrete or sand and cement screeds. If unsure, pour water on the surface - if it absorbs quickly, the primer is suitable; if not, priming isn't needed.
- New concrete must be at least 2 months old and washed with Floorsaver Floor Etcher to reduce alkalinity, remove weak residues and provide a key.

Step 2 – Repairs:

- Fill any holes using Floorsaver Pourable Concrete Filler.

Step 3 – Mixing:

- Stir the resin in the large tin and the curing agent in the small tin separately. Then pour the contents of the small tin into the large tin.
- Stir well using a wide tool such as a wooden batten, paint stirrer or drill-mounted mixing blade, making sure to scrape the sides and bottom so it's fully mixed.

Step 4 – Application:

- Now it's mixed you've got 2 hours to use it before it becomes unusable. Tip it into a roller tray or scuttle.
- Use a brush around the edges and a medium pile roller for the floor. One coat is all you need.

CURING TIMES:

PAINTING OVER THE PRIMER

As a guide, 8 hours at 15°C for water based coatings such as Floorsaver Epoxy Floor Paint, or 3-4 days with a solvent based coating such as Floorsaver Floor Paint.

SHELF LIFE:

12 months if unopened and should not be allowed to freeze.

WE DON'T RECOMMEND

- Applying to a previously painted, sealed or power floated surface since this primer relies upon absorption.
- Applying to self-levelling floor screeds.
- Applying to a wet surface. If residual damp remains after cleaning this is acceptable, but it cannot be applied to a wet surface as it will prevent the primer from penetrating.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments or need advice, please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888

IE: 0818 543 250

info@floorsaver.co.uk

info@floorsaver.ie

floorsaver.co.uk

floorsaver.ie