



Product Information Sheet:

Waterproof Roof Paint

5kg



Floorsaver Waterproof Roof Paint is a flexible, bitumen-based coating reinforced with rubber and fibre to waterproof and protect roofs. It won't sag or crack with heat or movement and can be used to stop leaks or extend roof life.

- Thick and flexible roof coating which protects against the elements
- One coat, high build application
- Suitable for use on roofing felt, porous asbestos-type sheets, corrugated iron, concrete and roof tiles.
- Can be used on wet surfaces as an emergency repair
- Can be mixed with sand to fill holes, cracks and splits
- Easy brush or roller application
- Black finish gradually fades to grey
- Get a few more years out of your roof!
- Can be applied in temperatures as low as 5°C

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- Preparation is quite minimal. Sweep off any moss, algae or dirt. If there has been a heavy fungal infestation use a fungicide and wash off.
- You can use Floorsaver Waterproof Roof Paint in the rain as an emergency. For long term repairs the surface should be as dry as possible. When coating large areas, we recommend that they are dry as trapped moisture can delay drying.

Step 2 - Repairs:

- Holes, cracks and splits can be filled using Waterproof Roof Paint mixed with dry sand to form a stiff mortar.
- Prime the repair with a coat of Waterproof Roof Paint, then trowel in the mortar.

Step 3 - Application:

- No need to stir.
- Easiest using a brush, but a roller is possible on flat, felted surfaces or on flat concrete.
- Aim to use 1kg per 1m².
- Clean equipment with White Spirit.
- Drying time approximately 24 hours.

TIP:

- If there are problem areas such as panel overlaps or felt joints, but you plan to coat the entire roof, apply a brush coat of Floorsaver Waterproof Roof Paint along these joins first. Let it dry, then coat the whole roof the following day.

WE DON'T RECOMMEND:

- Applying Waterproof Roof Paint to bare timber to try to form a waterproof seal.
- Application to EPDM or similar rubber roof membranes, as the product can soften rubber. Test on a small area if in doubt about product suitability.
- Applying in exceptionally hot temperatures.

SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments or need advice, please contact us using the details below.

Sales & Technical Support

UK: 0345 450 9888

IE: 0818 543 250

info@floorsaver.co.uk

info@floorsaver.ie

floorsaver.co.uk

floorsaver.ie